

1230

Heavy duty mortice lock, panic function E



Product profile

Same dimension as mortice locks 1105/1106

Panic function E: use knob/lever set (lever handle/female part on the inside, knob on the outside, spindle 5910 or 5911)

For emergency exits according to EN 179 in the non public area of the building

For panic exits according to EN 1125 in the public area of the building such as commercial buildings, schools and hospitals, administrations, airports, shopping malls

Standard version

Backset 60 mm

Forend satin stainless steel

Forend 230x18 mm, radiussed

Clamp follower 9 mm

Lock case blue galvanised

With steel latch

Latch damper

Single turn deadbolt in steel, 13 mm

Centres 78 mm

Cutout

1230.6 RZ - latch withdrawal

1230.7 PZ - latch withdrawal

Options

Backset 70 mm

Backset 80 mm

Package

single packaging

industrial packaging, 50 pces (left or right)

carpenter packaging, 50 pces (25 left / 25 right)

Standards

EN 1634-1: EI 30

EN 12209: 3M510F2HA30

Tested to EN 179 in combination with Glutz lever handle. For a current list of models please refer to our website: www.glutz.com

Tested to EN 1125 in connection with Glutz panic device 8615

Strike plates tested in sets: For rebated doors B-1151.711 For flush edged doors B-1001.431



Important note

On mortice locks for emergency / panic exit doors, cylinder with door knop must not be installed, and key must not be left in lock.

Heavy duty mortice lock, panic function E

