

82550 E Secure Box



Artikel Article	Aussenmasse mm Mesure extérieure mm			Innenmasse mm Mesure intérieure mm			Türdurchgang Passage de porte mm		Gewicht Poids kg	Inhalt Contenue l
	Höhe Hauteur	Breite Largeur	Tiefe Prof.	Höhe Hauteur	Breite Largeur	Tiefe Prof.	Höhe Hauteur	Breite Largeur		
82550.200	200	310	200	194	304	133	146	208	7	8
82550.225	250	350	250	240	340	200	195	252	10	16
82550.250	250	450	365	244	444	305	198	374	17	33
82550.380	380	350	360	374	344	309	320	260	16	40
82550.520	520	350	360	514	344	309	466	260	21	55

Product profile

Secure storage with eAccess RFID code reader, battery-operated.

The standard solution enables temporally limited, individually programmable access.

Opening and closing from outside take place with contact reading of the medium, such as a key tag or with entry of a PIN.

A mechanical key is available for emergency opening

Standard version

Identification via RFID Mifare DESfire EV 1 (ISO 14443A) or PIN

Programming via media or wireless access (868 MHz)

Housing design: Single-wall

Door design: Single-wall, 4 mm door leaf

Door locking: One side

Locking bolt: 15 mm thick

Door hinges: Internal

Anchor holes: 4 x rear wall, 4 x bottom

Paint: Dark grey

Electronic lock, 17 mm protrusion, batteries integrated, mech.

emergency opening lock with 2 keys

Options

82550.200: 200 x 310 x 200 (H x W x D)

82550.225: 250 x 350 x 250 (H x W x D)

82550.250: 250 x 450 x 365 (H x W x D)

82550.380: 380 x 350 x 360 (H x W x D)

82550.520: 520 x 350 x 360 (H x W x D)

Scope of supply

Secure box

2 x emergency key

4 x AA battery

Quick guide