

18938 MINT Combi

Multipoint lock, Combi (lever handle and key operated)



Product profile

The high-quality mechanical multipoint lock with integrated latch and lever handle locking. For use in house and apartment entrance doors / porch doors and in commercial buildings in difficult climatic conditions or in doors with a higher door seal pressure. Simple locking and unlocking via the lever handle followed by very smooth and easy securing over the cylinder. The dampened, reversible DIN L+R comfort latch ensures that the latch shoots out quietly and enters gently into the striking plate. The solid design, the hardened main bolt and the two hardened additional bolts make it possible to build door systems with a resistance class of up to RC3. The lock is approved for fire resistance and smoke protection tests in accordance with EN 1634. Can be combined with a wide range of Glutz fittings.

Standard version

- 4-part clamp follower, square 8/8.5/9 mm
- Lock case compatible with Glutz protection fittings
- Without latch withdrawal
- Simple locking and unlocking using the lever handle
- Very smooth securing via the cylinder; single throw
- Hardened main bolt; 20 mm throw
- Two additional hardened bolts; 20 mm throw
- Dampened, reversible DIN L+R comfort latch with latch blocking
- Simultaneous latch and lever handle blocking



Standards

Lever handle locking: Lockable lock follower, tested to 80 Nm in accordance with EN 12209.

Important note

The cylinder screw is not centred in the forend. To determine the cylinder lengths: centre of forend = centre of lock cylinder.

Do not use a reduction sleeve for the Follower/square spindle.

18938 · 1 · 2 · 3 · 4 · 5 · 6 · 7 · 8

	1 Cutout	2 Centres	3 Backset	4 Follower	5 Forend	6 Direction	7 Surface	8 Options
CH	02 RZ	78 78 mm	60 60 mm	8 8,0 mm	02 18r x 1788 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ		70 70 mm	9 9,0 mm	03 20r x 1788 mm	1 DIN R	99 On request	0090 Semi-circular arched doors
			80 80 mm					0110 Radiussed forend extension
DIN	1 Cutout	2 Centres	3 Backset	4 Follower	5 Forend	6 Direction	7 Surface	8 Options
	02 RZ	72 72 mm	65 65 mm	8 8,0 mm	03 20r x 1744 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ	74 74 mm	70 70 mm	9 9,0 mm		1 DIN R	99 On request	0090 Semi-circular arched doors
		92 92 mm	80 80 mm					0110 Radiussed forend extension
		94 94 mm						
0	1 Cutout	2 Centres	3 Backset	4 Follower	5 Forend	6 Direction	7 Surface	8 Options
	03 PZ	88 88 mm	65 65 mm	5 8,5 mm	03 20r x 1850 mm	0 DIN L	00 Stainless steel matt	0000 No options
			80 80 mm	9 9,0 mm		1 DIN R	99 On request	0090 Semi-circular arched doors
								0110 Radiussed forend extension

Multipoint lock, Combi (lever handle and key operated)

