

## 16610 Adjustable boxed striking plate 24 mm

Boxed striking plate as center striking plate



### Product profile

Boxed striking plate in stainless steel as center striking plate for latch/bolt. Integrated dummy component effeff 1418-13 ProFix® 2 with FaFix® adjustment. For the mortice and multipoint locks of the Glutz MINT family. Caused by the tensile ductility of the material and the sophisticated construction of the invisible angled screws, there will be reached highest resistance forces against deformation and pull out.

### Standard version

- X-Dimension (X-Mass): 8.5 mm (adjusting range 3 mm)
- Distance: 72-94 mm
- With: 24 mm
- Length: 210 mm
- Depth: 10 mm
- 3 special screws for invisible angled screwing
- 3 countersunk head screws for wood
- DIN L or R
- Matt stainless steel

### Options

- Black plastic push-fit box for covering the bolt mortice

### Important note

The dummy component 1418-13 ProFix® 2 is not approved for fire resistance and smoke protection tests in accordance with EN 1634.

For smoke and fire protection applications use: effeff dummy component 1410-F2 Feuerschutz ProFix® 2 or effeff universal-dummy component 1410-F6 Feuerschutz ProFix® 2.

Approved for RC3 door elements with a 3-point multipoint lock (EN 1627-1630).

Approved for RC4 door elements with a 5-point multipoint lock (EN 1627-1630).



DIN L

## 16610 Adjustable boxed striking plate 24 mm

Boxed striking plate as center striking plate

