

24100 Magnetic mortise lock with magnetic Delrin-latch



Product profile

Magnetic mortise lock with adjustable magnetic latch holder and steel main bolt. Suitable for all full leaf internal doors – rebated and square edged. As a complete set for steel frames or combined with the Glutz 22810 flat striking plate for wooden frames. The delrin magnetic latch technology offers several benefits.

The flush mounted latch in the forend allows for an elegant door leaf design. It can be installed as a flush flat striking plate without a lip, making scratches and damage to the paint on door frames a thing of the past. Cleaning is simpler as dust and grease can't build up. The entire system is very quiet thanks to the special damping of the delrin magnetic latch and the precise adjustability of the magnet depth. The delrin magnetic latch enables smooth adjustment of the door closer, as it doesn't cause resistance when running in.

Standard version

- Distance 78 mm
- Profile or round cylinder (with latch withdrawal):
- Backset 60, 70, 80 mm
- BB/WC: Backset 60, 70 mm
- Square clamp follower 8 mm
- WC follower 7 mm
- Forend 18 x 230 x 3 mm
- Forend radiussed, matt stainless steel
- Lock case compatible with Glutz fittings
- Magnetic latch with latch damper
- Adjustable magnetic latch holder: Depth: ± 3 mm, in steel frame cut out L/R: ± 1 mm
- Main bolt; throw 13 mm



24100 · ① · ② · ③ · ④ · ⑤ · ⑥ · ⑦ · ⑧

① Cutout	② Centres	③ Backset	④ Follower	⑤ Forend	⑥ Direction	⑦ Surface	⑧ Options
01 BB	78 78 mm	60 60 mm	8 8 mm	10 18 x 230 mm	0 DIN L [O]	00 Stainless steel matt	0000 No options
06 RZW		70 70 mm	9 9 mm		1 DIN R [O]	99 On request	
07 PZW		80 80 mm					
47 WC 7 mm							

24100 Magnetic mortise lock with magnetic Delrin-latch

