

24110 Mortise lock with magnetic latch









with magnetic Delrin-latch, latch blocking, panic E Product profile

Magnetic catch lock with adjustable magnetic latch holder, automatic latch blocking and panic E function. Suitable for all full-leaf internal doors – rebated and square edged. As a complete set for steel frames or combined with the Glutz 22820 flat striking plate for wooden frames. The delrin magnetic latch technology offers several benefits. The flush mounted latch in the forend allows for elegant door leaf design. It can be installed as a flush flat striking plate without a lip, making scratches and damage to the paint on door frames a thing of the past. Cleaning is simpler as dust and grease can't build up. The entire system is very quiet thanks to the special damping of the delrin magnetic latch and the precise adjustability of the magnet depth. The delrin magnetic latch enables smooth adjustment of the door closer, as it doesn't cause resistance when running in.



- Round or profile cylinder with latch withdrawal
- Distance 78 mm
- Backset 60, 70, 80 mm
- Square clamp follower 9 mm
- Forend radiussed 18 x 230 x 3 mm, matt stainless steel
- Lock case compatible with Glutz fittings
- Magnetic delrin latch with latch blocking and latch damper
- • adjustable magnetic latch holder: Depth: ± 3 mm, in steel frame cut out L/R: ± 1 mm

Standards

EN 1125: with Glutz 8615 stainless steel panic fitting.



24110 ·	1	٠	2	•	3	•	4	•	5	•	6	•	7	•	8	

Cutout	2 Centres	3 Backset	4 Follower	5 Forend	6 Direction	Surface	8 Options
06 RZW	78 78 mm	60 60 mm	8 8 mm	10 18r x 230 mm	0 DIN L (0)	00 Stainless steel matt	0000 No options
07 PZW	=	70 70 mm 80 80 mm	9 9 mm	-	1 DIN R (0)	99 On request	_



24110 Mortise lock with magnetic latch

with magnetic Delrin-latch, latch blocking, panic E 1 _L21.5 20.5 PΖ 68 64 16 10.5 10 35.5 10 18 50 Α Α 3.4 30 62 21.6 51 22 48 230 13 159 7.5 212 26 3.6 30 Ŋ 29. 16 13 72 Ø9 20 35.5 38 Ø5 18.3 DM 60...80 29 X = 4.55Y = 12-Z A-A X = 3.53 Z = 2...6