

18962 MINT SV PB

Multipoint lock, self-locking, panic B



Product profile

For main and side entrance doors with mechanically controlled lever handle operation in residential and commercial buildings. The panic B function with split lock follower and separated lever handle control (outside/inside) offers the ideal combination of access control and escape route. Access is controlled by permanently coupling/decoupling the outside lever handle via the cylinder. The solid construction is designed to withstand the highest shearing forces and counterforces in accordance with DIN EN 15685. This allows for construction of door systems with up to RC3 resistance class. Coupling (Decoupling) the outside lever handle: turn the key in opening direction (closing direction) until the drawback position.

Standard version

- Split 3-part lock follower; square 9 mm
- Mechanical coupling/decoupling of the outside lever handle (via the cylinder)
- Outside lever handle coupled: 11 mm bolt throw; very quiet; not security-relevant but max. fire resistance
- Panic B: panic side reversible inwards/outwards
- Simultaneous latch blocking and lever handle release when locked
- Three hardened bolts; 20 mm throw
- Slider protection: mechanical top/bottom
- Dampened, reversible DIN L+R comfort latch
- Suitable for rotary knob cylinders
- Follower turning angle 35°



Important note

The cylinder screw is not centred in the forend. To determine the cylinder lengths: centre of forend = centre of lock cylinder.

Do not use asymmetric cylinders with «L-cam».

Do not use a reduction sleeve for the Follower/square spindle.

No external, mechanical bolt-switch contact is recommended.

Only use the 5920 HESO panic-spindle.

Mount lever handles rotatably-fixed on plates/rosettes (easyfix®)!

18962 · 1 · 2 · 3 · 4 · 5 · 6 · 7 · 8

	1 Cutout	2 Distance	3 Backset	4 Follower	5 Forend	6 Direction	7 Surface	8 Options
CH	02 RZ	78 78 mm	60 60 mm	9 9,0 mm	02 18r x 1788 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ		70 70 mm		03 20r x 1788 mm	1 DIN R	99 On request	0090 Semi-circular arched doors
			80 80 mm					0110 Radiussed forend extension
DIN	02 RZ	72 72 mm	65 65 mm	9 9,0 mm	03 20r x 1744 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ	74 74 mm	70 70 mm			1 DIN R	99 On request	0090 Semi-circular arched doors
		92 92 mm	80 80 mm					0110 Radiussed forend extension
		94 94 mm						
O	03 PZ	88 88 mm	65 65 mm	9 9,0 mm	03 20r x 1850 mm	0 DIN L	00 Stainless steel matt	0000 No options
			80 80 mm			1 DIN R	99 On request	0090 Semi-circular arched doors
								0110 Radiussed forend extension

Multipoint lock, self-locking, panic B

