

18920 MINT SB PE

Multipoint lock, key operated, panic E



Product profile

For use in residential and commercial buildings, e.g. in side doors with emergency exit requirements (EN 179). The emergency exit function means that escape from the inside is possible at all times (lever handle). The solid design, hardened main bolt and two additional hardened bolts allow for construction of door systems up to RC3 resistance class.

Standard version

- Mechanical multipoint locking device
- Latch blocking and slider protection when locked
- 4-part clamp follower; square 9 mm
- Panic E: operation from outside via the cylinder/latch withdrawal (knob/pull handle)
- Smooth-running latch withdrawal for drawing back the latch
- Hardened main bolt; 20 mm throw
- Two additional hardened bolts; 20 mm throw
- Simultaneous latch blocking and slider protection when locked
- Dampened, reversible DIN L+R comfort latch
- Follower turning angle 35°

Important note

The cylinder screw is not centred in the forend. To determine the cylinder lengths: centre of forend = centre of lock cylinder.

Do not use a thumbturn cylinder. When using a standard cylinder the key has to be drawn-off.

Do not use a reduction sleeve for the Follower/square spindle.



18920 · ① · ② · ③ · ④ · ⑤ · ⑥ · ⑦ · ⑧

	① Cutout	② Centres	③ Backset	④ Follower	⑤ Forend	⑥ Direction	⑦ Surface	⑧ Options
CH	02 RZ	78 78 mm	60 60 mm	9 9,0 mm	02 18r x 1788 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ		70 70 mm		03 20r x 1788 mm	1 DIN R	99 On request	0110 Radiussed forend extension
			80 80 mm					
DIN	① Cutout	② Centres	③ Backset	④ Follower	⑤ Forend	⑥ Direction	⑦ Surface	⑧ Options
	02 RZ	72 72 mm	65 65 mm	9 9,0 mm	03 20r x 1744 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ	74 74 mm	70 70 mm			1 DIN R	99 On request	0110 Radiussed forend extension
		92 92 mm	80 80 mm					
		94 94 mm						
D	① Cutout	② Centres	③ Backset	④ Follower	⑤ Forend	⑥ Direction	⑦ Surface	⑧ Optionen
	03 PZ	88 88 mm	65 65 mm	9 9,0 mm	03 20r x 1850 mm	0 DIN L	00 Stainless steel matt	0000 No options
			80 80 mm			1 DIN R	99 On request	0110 Radiussed forend extension

Multipoint lock, key operated, panic E

