



83704 Double-knob E cylinder

EE / RZ



Product profile

Battery-powered electronic cylinder for internal and external doors. Opening and closing from both sides is done by contactless reading of the RFID medium or by the smartphone app and subsequent turning of the knob.

Standard version

- Exterior E knob with access control function and battery
- Interior E knob with access control function and battery
- Identification via RFID Mifare DESfire EV1/2 (ISO 14443A)
- Programming via media, wireless access (868 MHz)
- Protection class: IP56, EN 15684, RC2
- Fire protection EN 1634-2: 90 min
- BLE-ready

Options

- High exterior drill protection (PT1), up to RC4 (with corresponding door plate) Low temperature (LT) for operation below 0°C
- Shortened rib side A by 8mm (ST8), for protection fittings with plug-pulling protection

Scope of supply

- 1 double-knob E cylinder
- 2 batteries
- 1 retaining screw M5x75
- 1 Quick Guide

Important note

- Selection of weather conditions affects interior and exterior knob
- PT1 (drill protection) version only applicable for the external side

83704 · ① · ② · ③ · ④ · ⑤ · ⑥ · ⑦ · ⑧

① eAccess_Length A (External) II	② eAccess_Length B (Internal) II	③ eAccess_Operating conditions	④ Security	⑤ Turn type	⑥ Version	⑦ eAccess_Finish	⑧ eAccess_ Antenna colour
30,0 mm (Standard length)	30,0 mm	0 Standard	0 Standard	0 Digitalknauf	S Standard	0 Matt nickel	0 Black
35,0 mm	35,0 mm	1 Low temperature (LT)	2 PT1		M Cog 10	2 Polished chrome	1 White
40,0 mm	40,0 mm		4 ST8			3 Matt chrome	
45,0 mm	45,0 mm					5 Black	
50,0 mm	50,0 mm					7 Bronze effect	
55,0 mm	55,0 mm						
60,0 mm	60,0 mm						
65,0 mm	65,0 mm						
70,0 mm	70,0 mm						
75,0 mm	75,0 mm						
...						
160,0 mm	160,0 mm						

Lengths: Refer to the length matrix for available combinations.

Total length: min. 50mm, max. 220mm

Technical changes reserved 0723