

18945 MINT SV PE

Multipoint lock, self-locking, panic E



Product profile

For use in house and apartment entrance doors and in commercial buildings. Operation from outside takes place via the cylinder/latch withdrawal (knob/pull handle) or in conjunction with an E-fitting via identification systems (e.g. badge). The reversible DIN L+R comfort latch guarantees that the latch extends quietly and enters the striking plate gently. The solid design, hardened main bolt and two additional hardened bolts allow for construction of door systems up to RC3 resistance class. The lock is approved for fire resistance and smoke control tests in accordance with EN 1634.

Standard version

- Self-locking device with latch blocking and sequence control
- 4-part clamp follower, square 9 mm
- Panic E function
- Smooth-running latch withdrawal for drawing back the latch
- Hardened main bolt; 20 mm throw
- Two additional hardened bolts; 20 mm throw
- Slider protection: mechanical top/bottom
- Dampened, reversible DIN L+R comfort latch with latch blocking
- Suitable for rotary knob cylinders
- Follower turning angle 35°



Important note

The cylinder screw is not centred in the forend. To determine the cylinder lengths: centre of forend = centre of lock cylinder.

Do not use asymmetric cylinders with «L-cam».

Do not use a reduction sleeve for the Follower/square spindle.

No external, mechanical bolt-switch contact is recommended.

A knob/pull handle must be used on the outside.

18945 · 1 · 2 · 3 · 4 · 5 · 6 · 7 · 8

	1 Cutout	2 Centres	3 Backset	4 Follower	5 Forend	6 Direction	7 Surface	8 Options
CH	02 RZ	78 78 mm	60 60 mm	9 9,0 mm	02 18r x 1788 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ		70 70 mm		03 20r x 1788 mm	1 DIN R	99 On request	0090 Semi-circular arched doors
			80 80 mm					0110 Radiussed forend extension
DIN	02 RZ	72 72 mm	65 65 mm	9 9,0 mm	03 20r x 1744 mm	0 DIN L	00 Stainless steel matt	0000 No options
	03 PZ	74 74 mm	70 70 mm			1 DIN R	99 On request	0090 Semi-circular arched doors
		92 92 mm	80 80 mm					0110 Radiussed forend extension
		94 94 mm						
D	03 PZ	88 88 mm	65 65 mm	9 9,0 mm	03 20r x 1850 mm	0 DIN L	00 Stainless steel matt	0000 No options
			80 80 mm			1 DIN R	99 On request	0090 Semi-circular arched doors
								0110 Radiussed forend extension

Multipoint lock, self-locking, panic E

