Glutz

Access Since 1863

5466 | 5466K | 5435C | 5467

Stainless steel security plate ES 3

RC 4 ES3/SK4



Product profile

For burglar resistant doors RC 4 according to EN 1627 - 1630: 2011

Standard version

Outer plate 250 x 55 x 15 mm
Prepared for cylinder cover
Satin stainless steel
16 mm guide: Glutz glide inwards
5466 for door handle operation
5466K for door knob Operation

Inside plate 5435C 250 x 55 x 8 mm
Satin stainless steel
16 mm guide: Glutz glide inwards
Base plate with guide cam

Centres
PZ: 70 mm, 72 mm, 78 mm, 88 mm, 92 mm
RZ: 74 mm, 78 mm, 94 mm

Cylinder cover
No. 1: cylinder Projection: 7 - 12 mm
No. 2: cylinder Projection: 12 - 17 mm
No 3: cylinder Projection: 17 - 22 mm
No 4: cylinder Projection: 22 - 27 mm

Options

Polished stainless steel
RAL lacquered
PVD lacquered
16 mm twin, semi-outside
Glutz easyfix
Inner plate 5467 solid 250 x 55 x 6 mm
Inside plate 5436.2C conic 12 mm for SEAvision
Inside plate 5436.2C conic 18 mm
SEAvision Powerpack or KABA-Elostar

Standards

ES3-L-ZA, DIN 18257: 2003-03
Resistance class 4, EN 1906: 2002-05

Important note

When using in combination with KABA Elostar, it is essential to use long-type keys!