

82140 Controller E03 expanded

Gkutz Access Controller



Product profile

Flexible Controller for controlling doors, lift, locks, letterboxes plus other devices:

- up to 20 outputs and 12 inputs
- many interfaces
- designed for long life

Standard version

185 x 126 x 50 mm
12 - 24 V DC, typ. 6 W
DIN-rail or direct-mounting
2x fingerprint, 5x code
8x relays, 12x In, 12x Out
Ethernet
USB, I2C, Audio Out, 2x RS485 / RS232
access authorisation: two or four eye procedure
Logfile for movement and system data
List of user authorisations
Service functions: Network settings, software update via network, sensor test

Options

Controller options: interfaces to alarm systems, balancing, lift control, control of letterbox systems

- 216144 desktop mains unit 12 V DC / 70 W
- 216610 mains unit (DIN top-hat rail) 24 V DC / 1,3 A
- 216608 mains unit (DIN top-hat rail) 12 V DC / 1,9 A
- 216706 top-hat rail set for controller mounting
- 214640 Glutz USB Kit: for data protection and distribution of user database to several controllers
- 215436 socket strip for 4 relays or 4 In / Out (12-pole, black)
- 215443 socket strip for RS232/485 or 2 In/Out (6-pole, black)
- 215444 socket strip for Power Out (8-pole, orange)
- 215445 socket strip for Audio Out (8-pole, black)
- 215446 socket strip for Power In (6-pole, orange)