
Glutz

Access Since 1863

80520 E Organisation Fitting

Public, wide - steel - with square interior rose





Product profile

Battery-operated electronic organisation fitting for solid-leaf interior doors. Opening and closing from outside take place with contact reading of the RFID-medium. Door opening is always assured with the interior lever handle; EN179-compliant with suitable lever handle

Scope of supply

- E-fitting with interior rose
- Lever handle pair
- Battery pack
- Square spindle and screw set
- Quick guide

Standard version

- For DIN left-hand/right-hand doors
- Identification via RFID Mifare DESfire EV 1 (ISO 14443A)
- Programming via media or wireless access (868 MHz)
- External lever handle engaged, freewheeling

80520 · 1 · 2 3 · 4 · 5 6 · 7 · 8 · 9

1 Power supply	2 Cut-out outs. 3 Cut-out ins.	4 Distance	5 Lever handle design	6 Square spindle	7 Surface	8 Door thickness	9 Protection rose
00 Lithium Battery	**0** Blind	**00** Blind	**21** 53001 (5071) Memphis	**8** 8 mm	**00** Satin stainless steel	**01** 34 to 43 mm	**00 None/Blind**
	2 RZ	**55** 55 mm	**22** 53002 (5066) Savannah	**5** 8,5 mm	**11** Polished stain. steel	**02** 44 to 53 mm	
	3 PZ	**70** 70 mm	**23** 53004 (5064) Oslo	**9** 9 mm	**22** Polished brass	**03** 54 to 63 mm	
	4 PRZ	**72** 72 mm	**24** 53010 (5057) Thun		**33** Satin brass	**04** 64 to 73 mm	
		74 74 mm	**25** 53011 (5062) New Orleans		**44** Anti-bacterial	**05** 74 to 83 mm	
		78 78 mm	**26** 53013 (5098) Olten		**51** RAL 9005 black matt	**06** 84 to 93 mm	
		85 85 mm	**31** 53003 (5059) Oslo angled		**55** Wrought iron look	**07** 94 to 103 mm	
		88 88 mm	**32** 53012 (5072) Memphis angled		**99** Spec. execution	**08** 104 to 113 mm	
		90 90 mm	**33** 53009 (5066) Savannah angled				
		92 92 mm	**34** 50935 (5038) Lugano				
		94 94 mm	**35** 50937 (5040) Merkur				
			36 50936 (5038V) Lugano angled				
			37 50938 (50040) Merkur				
			39 50939 (50042) Merkur angled				
			40 50970 (50070) Appenzell				
			41 50971 (50071) Appenzell				
			99 Spec. execution				

RZ: 74, 78, 90, 94 mm; PZ: 55, 70, 72, 78, 85, 88, 90, 92 mm; PRZ: 74, 78, 90, 94 mm

Technical changes reserved 0324