

## 80551 E Organisation Fitting, WC

Public, narrow - steel - with interior plate




















## Product profile

Battery-operated electronic organisation fitting for metal frame interior doors with WC lock for reserved toilet systems in public areas, such as hospitals, retirement homes, restaurants, petrol stations, etc. Opening and closing from outside with wireless reading of the RFID-medium. The user locks the door from the inside with the thumbturn with the bolt of the WC lock. The door can be opened from inside with the handle lever when the bolt is retracted. The exterior plate has a red/green viewer.

## Standard version

- For DIN left-hand/right-hand doors
- Identification via RFID Mifare DESfire EV 1 (ISO 14443A)
- Programming via media or wireless access (868 MHz)
- External lever handle engaged, freewheeling

## Scope of supply

- E-fitting with interior plate
- Lever handle pair
- Battery pack
- Square spindle and screw set
- Quick guide

6 Square

spindle

8 8 mm

9 9 mm

**5** 8,5 mm

80551 · 🕕 · 🙎	3 . 4 . 5	6 . 7 .	8.9
Power supply	2 Cut-out outs.	4 Dis-	5 Leve
	Cut-out ins.	tance	

00 Lithium Battery 5 WC \* **78** 78 mm **90** 90 mm

ver handle design **72** 72 mm 21 53001 (5071) Memphis

22 53002 (5066) Savannah **23** 53004 (5064) Oslo 24 53010 (5057) Thun

25 53011 (5062) New Orleans 26 53013 (5098) Olten 31 53003 (5059) Oslo angled

39 50939 (50042) Merkur angled **40** 50970 (50070) Appenzell 41 50971 (50071) Appenzell 99 Spec. execution

32 53012 (5072) Memphis angled 33 53009 (5066) Savannah angled 34 50935 (5038) Lugano 35 50937 (5040) Merkur 36 50936 (5038V) Lugano angled 37 50938 (50040) Merkur

Surface 00 Satin stainless steel 11 Polished stain. steel 22 Polished brass

33 Satin brass 44 Anti-bacterial

51 RAL 9005 black matt 55 Wrought iron look 99 Spec. execution

8 Door thickness

Protection rose

00 None/Blind

**01** 34 to 43 mm **02** 44 to 53 mm

 54 to 63 mm 04 64 to 73 mm 74 to 83 mm 84 to 93 mm

**07** 94 to 103 mm **08** 104 to 113 mm

Thumbturn square: 7 mm, 8 mm