



80560 E Organisation Fitting

Public, narrow - steel - with square interior rose



Product profile

Battery-operated electronic organisation fitting for metal frame interior doors. Opening and closing from outside take place with contact reading of the RFID-medium. Door opening is always assured with the interior lever handle; EN179-compliant with suitable lever handle.

Scope of supply

- E-fitting incl. interior rose
- Lever handle pair
- Square spindle and screw set
- Battery pack
- Quick guide

Standard version

- For DIN left-hand/right-hand reversible doors
- Identification with RFID Mifare DESfire EV 1 (ISO 14443A)
- Programming via media or wireless access (868 MHz)
- Exterior handle engaged, freewheeling

80560 · 1 · 2 · 3 · 4 · 5 · 6 · 7 · 8 · 9

1 Power supply	2 Cut-out outs. 3 Cut-out ins.	4 Dis- tance	5 Lever handle design	6 Square spindle	7 Surface	8 Door thickness	9 Protection rose
00 Lithium Battery	0 Blind	00 Blind	21 53001 (5071) Memphis	8 8 mm	00 Satin stainless steel	01 34 to 43 mm	00 None/Blind
	2 RZ	55 55 mm	22 53002 (5066) Savannah	5 8,5 mm	11 Polished stain. steel	02 44 to 53 mm	
	3 PZ	70 70 mm	23 53004 (5064) Oslo	9 9 mm	22 Polished brass	03 54 to 63 mm	
	4 PRZ	72 72 mm	24 53010 (5057) Thun		33 Satin brass	04 64 to 73 mm	
		74 74 mm	25 53011 (5062) New Orleans		44 Anti-bacterial	05 74 to 83 mm	
		78 78 mm	26 53013 (5098) Olten		51 RAL 9005 black matt	06 84 to 93 mm	
		85 85 mm	31 53003 (5059) Oslo angled		55 Wrought iron look	07 94 to 103 mm	
		88 88 mm	32 53012 (5072) Memphis angled		99 Spec. execution	08 104 to 113 mm	
		90 90 mm	33 53009 (5066) Savannah angled				
		92 92 mm	34 50935 (5038) Lugano				
		94 94 mm	35 50937 (5040) Merkur				
			36 50936 (5038V) Lugano angled				
			37 50938 (50040) Merkur				
			39 50939 (50042) Merkur angled				
			40 50970 (50070) Appenzell				
			41 50971 (50071) Appenzell				
			99 Spec. execution				

RZ: 74, 78, 90, 94 mm; PZ: 55, 70, 72, 78, 85, 88, 90, 92 mm; PRZ: 74, 78, 90, 94 mm