

E-1130 Boxed striking plate for electric strikes 20 mm

Boxed striking plate as main striking plate

Product profile

Boxed striking plate in stainless steel as center striking plate for latch/bolt and electric strikes. Appropriate for electric strikes of the series Glutz compact electric strike A5xxx and fire protection electric strike FT5xx. For the Glutz mortice and multipoint locks. Caused by the tensile ductility of the material and the sophisticated construction of the invisible angled screws, there will be reached highest resistance forces against deformation and pull out.

Standard version

- X-Dimension (X-Mass): 4.25 mm (adjusting range 2.25 mm)
- X-Dimension MINT (X-Mass): 4.75 mm (electric strike with thickened adjusting piece; adjusting range 1.5 mm)
- Distance: 72-94 mm
- With: 20 mm
- Length: 210 mm
- Depth: 10 mm
- \bullet 3 special screws for invisible angled screwing
- 3 countersunk head screws for wood
- DIN L or R
- Matt stainless steel

Options

• Black plastic push-fit box for covering the bolt mortice

Important note

The electric strike must be equipped with the thickened adjusting piece for the locks of the MINT family.

For fire protection applications the Glutz fire protection electric strike FT5xx must be used.





DINL



E-1130 Boxed striking plate for electric strikes 20 mm

Boxed striking plate as main striking plate



