

# 19010 / 19015 HZ-lock RR

## Multifunctional security locking system



### Product profile

Three point locking device for security doors which complies with different requirements such as: burglar resistance up to resistance class 4, release by electronic access control, automatic self locking, emergency exit according to EN 179, weight of door leaf maximum 400 kg, fire- and smoke.

Panic function B with day-time function:

Lock purely mechanical: External lever handle permanently engaged by switchover via lock cylinder

Switchover to electrical day-time function: External lever handle engaged / self-locking switched off

### Standard version

Forend stainless steel 1724 x 24 x 6 mm

Backset 35 + 3 mm

Follower 9 x 9 mm

Centres: RZ 94 mm, PZ 92 mm

Reversible convenience latch with inclined inlet

Bolt extension 20 mm

Magnetic coil voltage 12 / 24 V DC

Control and lever contacts, lock contacts up to 30 V, 300 mA

Magnet, driven by access control

Monitoring contacts:

- lever handle outside / inside
- door Position
- door locking
- access by key

### Cutout

19010.2 RZ

19010.3 PZ

### Options

Electrical block of bolting mechanism (bolts locked during day-time operation)

Additional latch for electric strike

### Package

Single packaging

### Standards

RC4 to EN 1627-1630

DIN 18251-3, class 4

EN 179

EN 1634-1



# 19010 / 19015 HZ-lock RR

Multifunctional security locking system

