

24000

Heavy latch mortice lock with anti-friction lever latch (KF)



Product profile

For commercial buildings, offices, schools, hospitals and upmarket housing

Standard version

Backset 60 mm
Forend satin stainless steel
Forend 230x18 mm, radiussed
Clamp follower 9 mm
Lock case blue galvanised
Antifriction lever latch, crank in plastic material
Latch damper
Centres 78 mm

Package

Single packaging
Package, 10 pces (left or right)

Standards

EN 1634-1: EI 30
EN 12209: 3M510F-H020
Tested to EN 179 in combination with Glutz Lever handle.
For a current list of models please refer to our Website: www.glutz.com
Tested to EN 1125 in connection with Glutz Panic device 8615.



Important note

Please take care for the milling of the crank at the lock mortise. See dimension drawing.
The lock 24000 may not be used with adjustable strike plates. (for example V-1151)

24000 · ① · ② · ③ · ④ · ⑤ · ⑥ · ⑦ · ⑧

① Cutout	② Centres	③ Backset	④ Follower	⑤ Forend	⑥ Direction	⑦ Surface	⑧ Options
00 without	78 78mm	60 60mm	8 8mm	10 18r x 230 mm	0 DIN L	00 Stainless steel matt	0000 No options
06 RZW		70 70mm	9 9mm		1 DIN R	99 On request	
07 PZW		80 80mm					

Heavy latch mortice lock with anti-friction lever latch (KF)

